

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B08B 3/00		A1	(11) International Publication Number: WO 00/18521
			(43) International Publication Date: 6 April 2000 (06.04.00)
(21) International Application Number: PCT/US99/22532			(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 30 September 1999 (30.09.99)			
(30) Priority Data: 60/102,663 1 October 1998 (01.10.98) US 60/102,664 1 October 1998 (01.10.98) US 60/117,401 27 January 1999 (27.01.99) US			
(71) Applicant: MINNTECH CORPORATION [US/US]; 14605 28th Avenue North, Minneapolis, MN 55447 (US).			
(71)(72) Applicant and Inventor: STANLEY, Patricia, M. [US/US]; 3701 Pillsbury Avenue South, Minneapolis, MN 55409 (US).			
(74) Agents: WRIGLEY, Barbara, A. et al.; Minntech Corporation, 14605 28th Avenue North, Minneapolis, MN 55447 (US).			Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: **REVERSE FLOW CLEANING AND STERILIZING DEVICE AND METHOD**



(57) Abstract

A device (10) and method for cleaning and sterilizing tubular structures (94, 96) particularly narrow tubular structures (94, 96) such as lumens (14) of a medical device such as an endoscope (12) by reversing the flow of fluid in interconnected tubular structures (94, 96). The device comprises a first (80) and second (82) valve in fluid communication with a first (94) and second (96) tubular structure. The valves (80, 82) selectively switch between a first and second flow path within the tubular structures (94, 96), at least a part of the second flow path opposite the first flow path.

J1040 U.S. PTO
09/778286



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Title: REVERSE FLOW CLEANING AND STERILIZING DEVICE AND METHOD

This application claims the benefit of U.S. Provisional application No. 60/102,663, filed October 1, 1998; U.S. Provisional application No. 60/102,664, filed October 1, 1998; and U.S. Provisional application No. 60/117,401 filed January 27, 1999.

5 BACKGROUND OF THE INVENTION**1. Field of the Invention**

This invention relates generally to the field of sterilizing and cleaning tubular structures including long, narrow, tubular structures. In particular, it relates to a device and method for cleaning and sterilizing medical devices with lumens.

10

2. Description of the related art

Many tubular structures, in particular flexible fiber endoscopes, define long tortuous lumens. These lumens are typically from about 1 m to about 4 m long with inside diameters from about 0.5 mm to about 6 mm and frequently contain crevices, bends, connections, restrictions, and irregularities. These instruments are frequently used in diagnostic medicine, requiring penetration into the human body or other contact with the human bloodstream. It is, therefore, desirable that they are cleaned, rinsed, sterilized, disinfected, or otherwise treated with fluid chemical disinfectants or sterilants to prevent the cross contamination and transmission of pathogenic organisms from patient to patient. In order for fluid chemical sterilization to be effective, the chemical must reach all internal and external surfaces. Efficaciousness, therefore, is severely limited by the inherent irregularities present in the long, narrow, lumens of flexible fiber endoscopes making effective cleaning and sterilization difficult.

Consistently and quickly cleaning, disinfecting, and sterilizing medical devices is an important part of providing quality healthcare. Failure to consistently clean and sterilize medical instruments leads to unwanted transmission of bacteria, viruses, and other organisms to and from patients. Improper handling of medical instruments allows unwanted organisms access inside the body where they may cause infection and disease.

Although the terms "sterilization" and "disinfection" are sometimes used imprecisely, the medical industry and regulatory agencies have more precisely defined the following terms including subdividing disinfection into high, intermediate, and low level disinfection.

Sterilization is generally defined as the destruction or elimination of all microbial life forms. Operationally, a sterilizing process is one that destroys all microbes on a device that has been contaminated with 10^6 bacterial endospores.

High level disinfection is generally defined as the destruction or elimination of all microbial life forms except microbial spores. High level disinfectants however, must show a capability of destroying bacterial spores over an extended period of time.

Intermediate disinfection is generally defined as the destruction of all microbial life forms except bacterial spores and some viruses. However, intermediate disinfection requires the destruction or elimination of *Mycobacterium tuberculosis* var. *bovis*, which is a relatively difficult bacterium to destroy.

Low level disinfection is generally defined as the destruction of vegetative forms of bacteria (such as salmonellae and staphylococci), most fungi, medium sized or lipid containing viruses (such as herpes simplex virus, hepatitis B virus, and HIV), but not bacterial endospores, mycobacteria, or small or non-lipid viruses (such as poliovirus and rhinovirus).

The level of disinfection or sterilization desired for a particular piece of equipment generally depends on the degree of exposure the equipment poses to the patient. For example, sterilization is generally necessary for equipment that is introduced directly into the human body, either in contact with the blood stream, or in contact with normally sterile areas of the body. High level disinfection is generally required for equipment that contacts mucous membranes, but does not penetrate bodily surfaces. Low and intermediate disinfection is generally required for equipment that contacts unbroken skin.

Endoscopes, which are used to probe internal passages of the body, are an exception to the general rule of sterilizing equipment that is introduced directly into the human body. Ideally, all endoscopes should be cleaned and sterilized between uses. However, due to their delicate optical equipment, endoscopes remain an exception to the sterilization rule. The delicate optical equipment and lenses in these devices do not allow conventional methods of sterilization such as autoclaving, ethylene oxide gassing, or soaking for several hours in liquid sterilants. Autoclaving requires high temperatures for sterilization, which damages the optical lenses of the endoscopes. Ethylene oxide gas equipment is expensive and requires several hours to complete the sterilization and degassing process. Repeated soaking in liquid sterilants may also damage some endoscopes. In addition, the high cost of these specialized pieces of equipment demands efficient utilization of the instruments, requiring use of the same endoscope on as many patients in as little time as feasible. Therefore, soaking in liquid sterilants or sterilization by ethylene oxide gas is not economically feasible because of the long time period required. The demand for rapid reuse results in pressure to shorten or eliminate cleaning, disinfection, and sterilization practices. As a compromise to all of these

considerations, high level disinfection for endoscopes is conventionally accepted in lieu of sterilization.

Although high level disinfection has been conventionally acceptable, it does not provide the level of safety of sterilization. The conventional rationale for accepting the
5 reduced level of safety is that endoscopes contact mucous membrane and do not provide access to the blood stream. However, endoscopes are routinely used to find lesions in mucous membrane areas that may provide access to the blood stream. In addition, many endoscopes provide biopsy forceps that are miniature scalpels used to cut biopsy samples from the mucous membrane tissue. These common practices provide access to the bloodstream and a
10 potential pathway for unwanted organisms to access all parts of the body. In addition to providing a direct path to the bloodstream, many endoscopes such as duodenoscopes are used in normally sterile parts of the body. Introducing contaminated equipment into these areas has been shown to cause infection.

The lumens of medical devices have conventionally been difficult to clean, disinfect,
15 and sterilize. Some larger lumens may be cleaned with brushes. However, lumens that are too small for brushes are generally limited to cleaning by flushing with fluids such as water or air. As noted previously, the lumens also contain crevices, bends, connections, restrictions, and irregularities that restrict flow and hold residual material making cleaning difficult. Before a piece of equipment is disinfected or sterilized, it is preferably first cleaned. Failure
20 to completely clean residual material from the equipment potentially leaves microorganisms within and beneath the residual material not easily accessible to the disinfectant or sterilant.

Some conventional devices have used special attachments or caps to direct flow into different passages of endoscopes. However, these attachments create additional attachment points. The unexposed surfaces between the attachment and the medical device may not
25 receive complete cleaning or sterilization.

Typically, conventional devices and methods of cleaning have used uni-directional flow to clean long narrow devices with lumens. It is believed that irregularities and restrictions in the passages create air pockets or sheltered areas along the passages. For example, as the fluid flows around corners, the fluid tends to flow to the outside of the corner,
30 leaving an air pocket or undisturbed liquid or material on the inside edge. Fluid flow is also reduced on the downstream side of any restriction.

Some devices, such as those disclosed in Ishii 4,526,623, use suction from a syringe to draw residual fluid in the lumens or to draw fluid from an additional fluid container. However, the use of suction may collapse lumens, introduce additional air pockets in the

lumen, and create the need for additional attachments. Suction may also require the use of check valves to properly control the removal of fluid and reduce the amount of air introduced into the medical device. Check valves may also reduce or eliminate complete removal of the fluid. Cleaning by suction only removes liquid from multiple lumens until one lumen

5 contains air. Once a single lumen contains air, only air is drawn through the device because air flows more easily than liquid. The relative differences in the size of the lumens would also cause certain lumens to drain more quickly, leaving liquid in the remaining lumens. Lastly, the syringe method and device of Ishii is not easily automated.

10 Sterilization methods have also included immersion or soaking of medical devices in liquid sterilant. Sterilization by soaking typically requires several hours and air bubbles may become trapped inside the lumens, causing inconsistent results.

A new and useful device and method is needed that overcomes the problems associated with conventional methods of cleaning and sterilizing tubular structures, including long, narrow, tubular structures, particularly medical devices with lumens, by providing a
15 device and method that provides a reverse flow through the tubular structures.

SUMMARY OF THE INVENTION

It is an object of the reverse flow cleaning and sterilizing device and method in accordance with the present invention to solve the problems outlined above that have
20 heretofore inhibited the successful cleaning and sterilization of tubular structures, in particular, long, narrow, tubular structures.

More particularly, the apparatus and method of the reverse flow cleaning and sterilizing device in accordance with the present invention provides for the cleaning and sterilization of medical devices with lumens, particularly endoscope lumens.

25 The unique sterilization and cleaning device in accordance with the present invention broadly includes a first valve and a second valve. The first and second valves are each in fluid communication with a fluid supply at a positive pressure. The first valve is in fluid communication with a first tubular structure having a proximal end and a distal end with the first valve in fluid communication with the proximal end. The second valve is in fluid
30 communication with a second tubular structure having a proximal and a distal end with the second valve in fluid communication with the proximal end. The first tubular structure is in fluid communication with the second tubular structure. The first and second valves selectively switch between a first position and a second position. The first position causes a first fluid flow path and the second position causes a second fluid flow path. At least part of

the second fluid flow path is opposite the first fluid flow path. In the first position the first valve is open to the fluid supply and the second valve is closed to the fluid supply. In the second position the second valve is open to the fluid supply and the first valve is closed to the fluid supply.

- 5 The device may also provide that either both fluid flow paths start at one end of a medical device or one fluid flow path may start in a control head or center of the medical device.

The device may also provide that the distal end of at least one of the tubular structures is open to a drain at about atmospheric pressure.

- 10 The device may also provide that in the first position the second valve is open to a drain line and in the second position the first valve is open to a drain line.

The device may also provide that the fluid supply has a flow volume from about 100 ml/min to about 1400 ml/min and a flow velocity from about 50 cm/sec to about 500 cm/sec and a pressure below about 20 psi for about 1 minute to about 20 minutes.

- 15 The device may also provide a third and a fourth valve, a third and a fourth tubular structure, and a third and a fourth position.

The device may also be used in an automatic reprocessing device so that a central processor controls positioning of the valves.

- 20 The apparatus and method in accordance with the present invention provides both a method of sterilization of tubular structures and a method of cleaning the lumens of a medical device.

- 25 The sterilization method broadly includes the sterilization of the interior of a tubular structure comprising: a) providing a tubular structure, b) providing a sterilizing fluid c) causing the sterilizing fluid to flow at a positive pressure through the tubular structure in a first fluid flow path, and d) causing the sterilizing fluid to reverse flow at a positive pressure through the tubular structure in a second fluid flow path, so that at least part of the second fluid flow path is opposite the first fluid flow path.

The sterilization method may also include providing the sterilizing fluid at a temperature from about 20 degrees C to about 50 degrees C and from about 1 minute to about 20 minutes.

- 30 The sterilization method may also include providing a tubular structure having a diameter equal to or less than about 6 mm and the flowing and the reverse flowing have a flow velocity from about 50 cm/second to about 500 cm/second, a flow volume from about 100 ml/min to about 1400 ml/min, and a pressure below about 20 psi.

The sterilization method may also include starting the first fluid flow path and starting the second fluid flow path in one end of a medical device.

The device may also provide that one fluid flow path may start in a control head or other attachment point of the medical device.

5 The sterilization method may also include providing the device of the present invention.

The sterilization method may also include controlling the flowing and the reverse flowing by a central processor.

The present invention may also include a method of cleaning a medical device with lumens. The cleaning method broadly includes a method of cleaning the lumens of a medical
10 device including a) providing a medical device with a first lumen and a second lumen, each lumen having a proximal end and a distal end, the first lumen in fluid communication with the second lumen, and the second end of at least one of the lumens open to a drain at about atmospheric pressure; b) providing a cleaning fluid; c) causing the cleaning fluid to flow at a positive pressure through the lumens in a first fluid flow path starting at the proximal end of
15 the first lumen; and d) causing the cleaning fluid to reverse flow at a positive pressure through the lumens in a second fluid flow path starting at the proximal end of the second lumen, such that at least part of the second fluid flow path is opposite the first fluid flow path.

The cleaning method may also include providing a medical device with the first end of each lumen located in the same end of the medical device.

20 The cleaning method may also provide that either both fluid flow paths start at one end of a medical device or one fluid flow path may start in a control head or other attachment point of the medical device.

The cleaning method may also include draining the first fluid flow path through the proximal end of the second lumen and draining the second fluid flow path through the
25 proximal end of the first lumen.

The cleaning method may also include providing the flowing and the reverse flowing at a flow velocity of from about 50 cm/sec to about 500 cm/sec, a flow volume from about 100 ml/min to about 1400 ml/min, and a pressure below about 20 psi.

The cleaning method may also include providing the device of the present invention.

30 The cleaning method may also provide controlling the flowing and the reverse flowing by a central processor.

One advantage of the present invention is improved sterilization. The present invention provides better application of the fluid to all parts of the interior of tubular

structures. Improved application of the fluid to the interior of the tubular structure results in faster and more consistent sterilization.

Another advantage is that air pockets are consistently removed. The present invention improves sterilization and cleaning by providing better application of fluid by consistently removing air pockets from the interior of the tubular structures. Flowing and reverse flowing at a positive pressure provides consistent removal of air pockets. Soaking or holding fluid in the tubular structures does not consistently remove air pockets resulting in inconsistent cleaning and sterilization.

Another advantage is that the fluid obtains improved access to cracks, crevices, and restrictions. Flowing and reverse flowing at a positive pressure forces fluid into cracks, crevices, and restrictions from more than one direction. Flowing from one direction or flowing at a negative pressure does not force fluid into the cracks and crevices, especially downstream of a restriction, causing inconsistent sterilization and cleaning.

Another advantage is that residual liquids and materials remaining in the lumens are more adequately displaced with fluid. Liquid, such as left over rinse water may not be completely displaced using an uni-directional flow pattern. As a result, the chemicals (active ingredients) in the fluid must diffuse into the rinse water before sterilization may occur. The present invention provides better displacement of residual materials and liquids providing faster and more consistent sterilization and cleaning.

Another advantage is that soaking is not required. The present invention is not limited by the use of large volumes of sterilizing fluid needed to immerse the entire tubular structure, saving sterilization fluid.

Another advantage is that sterilization can be accomplished more quickly. Long soaking times of hours required for immersion sterilization may be reduced to about minutes for the present invention. Quicker sterilization results in better utilization of medical equipment.

Another advantage is that sterilization can be accomplished more consistently. Flowing sterilizing fluid from more than one direction and forcing the sterilizing fluid into cracks and crevices with positive pressure reaches the interior surfaces of tubular structures more consistently. More consistent application of the sterilizing fluid to the interior surfaces provides more consistent sterilization.

Another advantage is that the present invention can be attached to the supply ports of the endoscope. The present invention may be attached to one end of a medical device such as an endoscope without any attachments to the distal end or insertion section of the medical

device. Other methods using suction pressure require the attachment of a fluid source in addition to the suction source requiring additional attachments. A device that connects to one end of the medical device provides an easier and more centralized attachment and eliminates the need for additional attachments.

5 Another advantage is that the present invention provides an alternative method of attachment to the air/water channel, particularly if the device does not have a gas or CO₂ channel. The present invention may provide for attachment to the air/water channel at the air/water control cylinder.

10 Another advantage is that the present invention reduces the number of attachments that cause additional contamination points. Each additional attachment creates an area between the attachment and the medical device that is difficult to reach with fluid. The more attachments the greater the inconsistency of cleaning and sterilization.

15 Another advantage is that the present invention uses positive pressure flow. In addition to the improved penetration capabilities previously described, positive pressure flow is easier to provide. Positive pressure provides a greater range of pressures and can be more easily provided through a greater variety of positive pressure pumps. Positive pressure flow provides both the pressure source and the fluid source at one location, simplifying connections and automation. Positive pressure is also safer because contaminants cannot be drawn into the device through leaks in the system.

20 Another advantage of the present invention is that it may be operated at temperatures less than 50 degrees C. Operating at temperatures below 50 degrees C prolongs the life of medical devices and reduces burn hazards.

25 Another advantage is that the present invention may be easily automated. The use of valves controlled by a central processor may be easily automated, particularly in an automatic reprocessing device. The elimination of manually operated equipment and methods such as syringes provides for automation.

30 These and other objects and advantages of the present invention will become apparent during the course of the following detailed description and appended claims. The invention may best be understood with reference to the accompanying drawings, wherein an illustrative embodiment is shown.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic drawing of the device in a first flow position.

Fig. 2 is a schematic drawing of the device in a second flow position.

Fig. 3 is a side cross sectional view of an endoscope connected to the device showing a first and a third fluid flow path.

5 Fig. 4 is a side cross sectional view of an endoscope connected to the device showing a second and fourth fluid flow path.

Fig. 5 is a schematic drawing of the device in an alternate second flow position.

Fig. 6 is a schematic drawing of the device in an alternate first flow position.

Fig. 7 is a side cross sectional view of an endoscope connected to the device showing an alternate first fluid flow path.

10 Fig. 8 is a side cross sectional view of an endoscope connected to the device showing an alternate second fluid flow path.

Fig. 9 is a schematic drawing of the device incorporated into an automatic endoscope reprocessing machine controlled by a central processor.

15 Fig. 10 is a schematic drawing of the device incorporated into an alternate embodiment of an automatic endoscope reprocessing machine controlled by a central processor.

Fig. 11 shows an exterior perspective view of a medical instrument reprocessing device having one of a pair of chemical supply drawer access doors in an open position and one of a pair of reprocessing bay cabinet access doors in an open position.

20 Fig. 12 shows a perspective view of the major components of a medical instrument reprocessing device in one possible arrangement relative to each other and positioned in a representation of the compartmentalization provided by an exterior housing. Two reprocessing bays are represented in the reprocessing bay cabinet of the housing; one configured with a reprocessing bay door in the open position and the other, presented in broken lines, configured without the necessary reprocessing bay door.

25 Fig. 13 shows a perspective view of two reprocessing bays, without access panels, of a medical instrument reprocessing device. One reprocessing bay is shown in a partial sectional view disclosing an exterior pressure washing assembly.

30 Fig. 14 shows a perspective sectional view of a heater assembly of a medical instrument reprocessing device invention.

Fig. 15 shows a front elevational view of the movable cassette assembly of a medical instrument reprocessing device.

Fig. 16 shows a schematic representation of the hydraulic system and pneumatic system of a medical instrument reprocessing device.

DETAILED DESCRIPTION OF THE INVENTION

GENERAL ASSEMBLY

Referring to Figures 1, 2, 5, 6, 9, and 10, the device 10 in accordance with the present invention broadly includes a first valve 80 and a second valve 82. However, additional valves for additional tubular structures may be provided. The first and second valves 80, 82 are each in fluid communication with to a fluid supply 84 at a positive pressure. The first valve 80 is in fluid communication with a first tubular structure 94, the first tubular structure 94 having a proximal end 98 and a distal end 100, the first valve 80 is in fluid communication with the proximal end 98. The tubular structures typically have a length that is about 200 to about 8,000 times the inside diameter. The second valve 82 is in fluid communication with a second tubular structure 96, the second tubular structure 96 having a proximal end 102 and a distal end 104, the second valve 82 is in fluid communication with the proximal end 102. The first tubular structure 94 is in fluid communication with the second tubular structure 96. The first and second valves 80, 82 selectively switch between a first position 106 and a second position 108. In the first position 106, the first valve 80 is open to the fluid supply 84 and the second valve 82 is closed to the fluid supply 84. In the second position 108 the second valve 82 is open to the fluid supply 84 and the first valve 80 is closed to the fluid supply 84. The first position 106 causes a first fluid flow path 110 and the second position 108 causes a second fluid flow path 112. At least a part of the second fluid flow path 112 is opposite the first fluid flow path 110.

The device 10 may also provide that the distal end 100, 104 of at least one of the tubular structures 94, 96 is open to a drain 114 at about atmospheric pressure.

The device 10 may also provide that in the first position 106 the second valve 82 is open to the drain line 88 and in the second position 108 the first valve 80 is open to the drain line 88.

The device 10 may also provide that the fluid supply 84 has a flow volume from preferably about 100 ml/min to about 1400 ml/min. Preferably the flow volume is about 100 ml/min to about 250 ml/min for tubular structures of about 1 mm to about 2 mm in diameter and about 600 ml/min to about 1400 ml/min for tubular structures of about 3 mm to about 6 mm in diameter. The fluid supply 84 has a flow velocity from preferably about 50 cm/sec to about 500 cm/sec and most preferably about 50 cm/sec to about 250 cm/sec. The fluid supply 84 has a pressure preferably below about 20 psi and most preferably from about 10 psi to about 20 psi. Pressures above about 20 psi may damage the endoscope and are not

recommended by manufacturers. The sterilizing fluid 116 is preferably provided for about 1 minute to about 20 minutes and most preferably about 10 minutes.

The device 10 may also provide a third and a fourth valve, a third and a fourth tubular structure, and a third and a fourth position.

5 The device 10 may also be used in an automatic reprocessing device so that a central processor controls positioning of the valves.

The device 10 may be used to process a medical device with lumens such as an endoscope 12 described below. Endoscopes may be about 1 m to about 4 m long and have lumens ranging from about 0.5 mm to about 6 mm.

10 As shown in Figures 3,4 7, and 8, endoscope 12 may have a plurality of tubular structures or lumens 14. The lumens 14 typically consist of a water channel 16, a suction channel 18, an air channel 20, and a CO₂ channel 22. The endoscope 12 typically has an insertion section 24 extending from a control section 26 and an umbilical section 28 also extending from the control section 26. The lumens 14 are defined inside the endoscope 12 and extend through the
15 endoscope 12 from the insertion section 24 and are in fluid communication with control valve cylinders 30 and extend and are in fluid communication with the lumens 14 in the umbilical section 28. There are typically three control valve cylinders 30 including an air/water cylinder 32, a suction cylinder 34, and a CO₂ cylinder 36.

20 UMBILICAL SECTION

During use, the light guide or umbilical section 28 of the endoscope 12 connects the lumens 14 of the endoscope 12 to a supply of suction air, water, and CO₂ via supply ports located at the distal end 52 of the umbilical section 28. The lumens 14 include an air channel 20, a suction channel 18, a water channel 16 and a CO₂ channel 22. The umbilical section has
25 a suction supply port 38 in fluid communication with the suction channel 18, a CO₂ supply port 40 in fluid communication with the CO₂ channel 22, an air supply port 44 in fluid communication with the air channel 20, and an air/water supply port 42 in fluid communication with the water channel 16 and the air channel 20. The lumens 14 extend through the umbilical section 28 and are in fluid communication with the control cylinders 30
30 located in the control section 26.

CONTROL SECTION

The control section 26 is located in the middle of the endoscope 12 and contains the control cylinders 30 and the lens 132 for viewing through the endoscope 12. During normal

operation, the control cylinders 30 contain control valves and provide operational control of the flow of air, water, and CO₂. During processing, cleaning, and sterilization, the control valves are removed from the air/water control cylinder 32 and the suction cylinder 34 and the openings are capped. The CO₂ control valve in the CO₂ cylinder 36 is left in the open position. The CO₂ cylinder 36 is in fluid communication with both the CO₂ channel 22 from umbilical section 28 and the CO₂ channel 22 that is in fluid communication with the air channel 20 between the air/water cylinder 32 and the insertion section 24. The air/water cylinder 32 is in fluid communication with four channels, a) the air channel 20 from the umbilical section 28, b) the water channel 16 from the umbilical section 28, c) the air channel 20 from the insertion section 24, and d) the water channel 16 from the insertion section 24. The insertion section 24 typically has three instead of four lumens because the CO₂ channel 22 joins and is in fluid communication with the air channel 20 in the control section 26 downstream of the control cylinders 30.

15 INSERTION SECTION

The insertion section 24 is connected to the control section 26 of the endoscope 12 and is the portion of the endoscope 12 that is inserted into the patient during use. The insertion section 24 has an air/water nozzle 46 and a suction opening 48 located at the distal end 54 of the insertion section 24. The water channel 16 and air channel 20 merge in the insertion section 24 to form an air/water channel 56. The air/water channel 56 is in fluid communication with the air channel 20 and the water channel 16 and with the air/water nozzle 46. The air channel 20 is in fluid communication with the air/water cylinder 32 and with the air/water channel 56. The water channel 16 is in fluid communication with the air/water cylinder 32 and with the air/water channel 56. The suction channel 18 is in fluid communication with the suction cylinder 34 and with the suction opening 48. The endoscope may also have a forceps or biopsy port 50 located in the control section 26. The biopsy port 50 is in fluid communication with the suction channel 18 between the suction cylinder 34 and the suction opening 48.

30 SUCTION CHANNEL

The suction channel 18 is typically from about 3 mm to about 6 mm in diameter. The suction channel 18 can be subdivided into an umbilical suction channel 18a, a control suction channel 18b and an insertion suction channel 18c. The umbilical suction channel 18a is the portion of the suction channel 18 from the suction supply port 38 to the suction cylinder 34.

The control suction channel 18b is the portion from the suction cylinder 34 to the biopsy port 50. The insertion suction channel 18c is the portion from the biopsy port 50 to the suction opening 48.

5 AIR CHANNEL

The air channel 20 is typically from about 1 mm to about 2 mm in diameter. The air channel 20 can be subdivided into an umbilical air channel 20a, a control air channel 20b, and an insertion air channel 20c. The umbilical air channel 20a is the portion from the air/water supply port 42 and the air supply port 44 to the air/water cylinder 32. The control air channel
10 20b is the portion from the air/water cylinder 32 to the CO₂ channel 22. The insertion air channel 20c is the portion from the CO₂ channel 22 to the air/water channel 56.

WATER CHANNEL

The water channel 16 is typically from about 1 mm to about 2 mm in diameter. The water
15 channel 16 can be subdivided into an umbilical water channel 16a and an insertion water channel 16c. The umbilical water channel 16a is the portion from the air/water supply port 42 to the air/water cylinder 32. The insertion water channel 16c is the portion from the air/water cylinder 32 to the air/water channel 56.

20 CO₂ CHANNEL

The CO₂ channel 22 is typically from about 0.5 to about 2 mm in diameter. The CO₂ channel 22 is particularly complex and restricted in the CO₂ valve. The CO₂ or gas valve utilizes narrow passages and restrictions. The CO₂ channel 22 may be subdivided into an umbilical CO₂ channel 22a, and a control CO₂ channel 22b. The umbilical CO₂ channel 22a is
25 the portion from the CO₂ supply port 40 to the CO₂ cylinder 36 and the control CO₂ channel 22b is the portion from the CO₂ cylinder 36 to the air channel 20.

THE DEVICE

30 As previously described and as shown in Figures 1 through 10, the device 10 broadly includes a first valve 80 and a second valve 82. The first and second valves 80, 82 are each in fluid communication with a fluid supply 84.

In the preferred connection to an endoscope, the first valve 80 is in fluid communication with the CO₂ supply port 40 and the second valve 82 is in fluid communication with the

air/water supply port 42. The connection to the air/water supply port 42 may also preferably include a connection to the air supply port 44 using a T-connection. In addition, either valve 80, 82 may be connected to either the CO₂ supply port 40 or the air/water supply port 42.

5 In an alternative connection to an endoscope, the first valve 80 is in fluid communication with the air/water supply port 42 and the second valve 82 is in fluid communication with the air/water cylinder 32. The connection to the air/water supply port 42 may also include a connection to the air supply port 44 using a T-connection. In addition, either valve 80, 82 may be connected to either the air/water cylinder 32 or the air/water supply port 42.

10 The valves 80, 82 are preferably three-way valves that provide three connections to the valve and allow flow between any two connections. However, the valves may be two-way valves or a combination of two-way valves. Preferably one connection is in fluid communication with the fluid supply 84, a second connection is connected to a first tubular structure 94, and one connection is connected to a second tubular structure 96. The valves 80, 82 are preferably Predyne B3314 three way valves with 1/8 inch NPT threads and a fluid
15 constant (Cv) of 0.11. The valves 80, 82 may be in fluid communication with the tubular structures 94, 96 by any means known in the art such as tubing and flexible couplings.

The connecting lines 134, including the fluid supply 84 and the drain line 88 may be of any material used in sterilizing and cleaning processing equipment. The connecting lines are preferably about 1/4 inch to about 1/2 inch diameter plastic tubing, preferably polyethylene.

20 The device 10 may also include a blocking valve 118 in the fluid supply 84 to direct the flow of fluid to a limited number of tubular structures. Limiting the flow to one or two lumens allows the use of a smaller fluid supply pump. Limiting the flow to one lumen at a time also assures that each lumen receives adequate flow and is not affected by different lumen sizes or by blockages. The blocking valve 118 may also be used in testing procedures
25 to determine if blockages exist in the lines or lumens.

The fluid may consist of a cleaning fluid 86, a sterilizing fluid 116, or any other fluid that is desired to reach all portions of the tubular structure 94,96. The fluid may be a liquid or a gas. The sterilizing fluid 116 may comprise a liquid performic acid based sterilant, as described in provisional application 60/102,664 entitled MULTI-PART ANTI-MICROBIAL
30 CONCENTRATE SYSTEM ACTIVATED FLUID, USE-DILUTION FLUID, METHOD OF MAKING SAME, AND METHOD OF STERILIZING WITH THE USE-DILUTION. FLUID, filed on October 1, 1998, the disclosure of which is hereby incorporated by reference.

The device and method of the present invention may be incorporated into an endoscope reprocessing device, as described in provisional application 60/102,663 entitled
ENDOSCOPE REPROCESSING AND STERILIZATION SYSTEM, filed on October 1,
1998, the disclosure of which is hereby incorporated by reference. Figures 11-16 and the
5 following description of the medical reprocessing device are from the above described
provisional application.

AUTOMATIC MEDICAL INSTRUMENT REPROCESSING DEVICE

Referring now to Figures 11-15, an endoscope reprocessing and sterilization system is
10 shown and generally indicated as 810. An exterior housing 812 is provided to arrange,
contain and provide protection for the components of the reprocessing system 810. A
reprocessing bay cabinet 814 of the housing 812 is configured to contain at least one
reprocessing bay 816. The reprocessing bay cabinet 814 is equipped with at least one cabinet
access door 818. The embodiment shown in Fig. 11 is configured to have two cabinet access
15 doors 818a, 818b which are shown with one cabinet access door 818a in the open position
allowing access to the at least one reprocessing bay 816 and the other cabinet access door
818b in the closed position. The preferred embodiment shown in Figures 11-12 is configured
to have two independently operated reprocessing bays 816a, 816b, although it is not limited
to two independently operated reprocessing bays 816.

20 A chemical supply drawer 820, which is configured to contain support components,
generally indicated at 822, is equipped with at least one drawer access door 824.

The embodiment shown in Fig. 11 is configured to have two chemical supply drawer
access doors 824a, 824b which are shown with one drawer access door 824a in the open
position allowing access to the support components 822 and the other drawer 820 access door
25 824b in the closed position. The support components 822, contained within the chemical
supply drawer 820, can include a soap container 826, a plurality of chemical sterilant
component containers 828, 830, a water heater 832, a hot water tank 834, a reaction chamber
836, a load sensor 838, an electric motor and pump 840, an air compressor 842, and a
compressed air tank 844. The preferred embodiment shown in Fig. 12 is configured with two
30 chemical sterilant component containers 828, 830 which serve to contain the two components
of a multi-component concentrate system. The reprocessing system 810 may include a
greater or lesser number of chemical sterilant component containers depending upon the
number of components required for the sterilant used. In the preferred embodiment, each of
the two reprocessing bays 816a, 816b is independently operated. To support such

independent operation, the device 810, as shown in Fig. 12, is equipped with an independently operated electric motor and pump 840a, 840b, one for each reprocessing bay 816a, 816b.

5 Hydraulic and pneumatic connections between each of the components contained within the chemical supply drawer 820 and the reprocessing bays 816a, 816b contained within the reprocessing bay cabinet 814 are shown only in Fig. 16 to simplify presentation of the major components shown in Figures 11-15.

The reprocessing bays 816a, 816b are identically configured and independently operated. Detail discussion of the reprocessing bay components and operations will, for
10 demonstration purposes, be limited to descriptions of reprocessing bay 816a.

The reprocessing bay 816a is equipped with a reprocessing bay door 846, which serves to seal the reprocessing bay during operation. The reprocessing bay door 846 can be constructed so as to provide thermal and sound proofing features. The vertical side walls 848a, 848b, back wall 850, ceiling member 852, and floor member 854 can also be formed to
15 provide thermal and sound proofing features. The thermal and sound proofing features can be provided by manufacturing the side walls 848a, 848b, back wall 850, ceiling 852, floor 854, and door 846 structures of materials such as, for example, plastics, steel, glass, and the like.

The reprocessing bay 816a is equipped with at least one and preferably two identical rotating arm members 856. In the preferred embodiment, the two rotating arm members
20 856a, 856b are separately rotatably mounted on a central portion of opposing side walls 848a, 848b. The following detailed description applies to all rotating arm members 856 but reference is limited to rotating arm member 856a, which is best shown in Fig. 13. The rotating arm member 856a includes a central hub sleeve 858 rotatably connected around a rotating arm hub member 860 which extends outwardly at about a right angle from the central
25 portion of side wall 848a. At least two counterbalanced spray arms 862a and 862b are connected on approximate opposing sides of the central hub sleeve 858. Each spray arm 862a, 862b defines a spray arm lumen 864a, 864b (shown in part with broken lines). The spray arm lumen 864a, 864b extends at least a portion of the length of the spray arm 862a, 862b and serves to operatively connect a hub sleeve lumen 866 defined within the central hub
30 sleeve 858 with a plurality of spray jets 868 defined in the wall of the spray arms 862a, 862b. Together the interconnected hub sleeve lumen 866, spray arm lumens 864a, 864b and spray jets 868 provide a conduit for the pressurized flow of washing, rinsing and sterilizing fluids from a rotating fluid connector 870, defined within the hub member 860, to the interior of the reprocessing bay 816a. The washing, rinsing and sterilizing fluids are provided to the

rotating fluid connector 870 by tubular conduits as shown in Fig. 16. Optionally, one or more of the side walls 848a, 848b, back wall 850, ceiling 852, floor 854 and door 846 members walls of the reprocessing bay can be provided with wall spray jets 869 which are fluidly connected to the rotating fluid connector 870 or, alternatively, to a separate fluid inlet connector. Tubular conduits used in the present invention can be formed of metal, plastic, glass and the like as is well known in the art.

At each distal end 872a, 872b of spray arms 862a, 862b is a spray nozzle 874a, 874b, which is configured with a plurality of spray openings 876. The spray openings 876 are operatively connected to the spray arm lumens 864a, 864b and together with the spray jets 868 direct sterilant and rinse fluids into the central portion of the reprocessing bay 816a. Spray nozzles 874a, 874b may also rotate about the longitudinal axis of spray arms 862a, 862b. In addition to the fluid directing function for sterilizing and rinsing, the spray openings 876 and spray jets 868 direct the pressurized flow of fluid out of the spray nozzle 874a, 874b and spray arms 862a, 862b in such a manner as to effect aggregate impulse which produces a reactive rotational force of the spray arms 862a, 862b around the central hub 860.

The reprocessing bay 816a can have at least one cassette guide 878 which serves to guide a cassette 880 from a loading position outside of the reprocessing bay 816a to an operational position inside the reprocessing bay 816a. Preferably the reprocessing bay 816a is equipped with two cassette guides, an upper cassette guide 878a and a lower cassette guide 878b. The upper cassette guide 878a can be secured to the ceiling 852 or alternatively to the upper portion of the back wall 850 of reprocessing bay 816a. The lower cassette guide 878b can be secured to the floor 852 or alternatively the lower portion of the back wall 850 of reprocessing bay 816a. The interior surface of the door 846 of reprocessing bay 816a can be configured to have a door guide 882 which aligns with the lower cassette guide 878b to facilitate the positioning of the cassette 880 into or out of the reprocessing bay 816a.

The cassette 880 is configured to removably secure a medical device such as an endoscope within the reprocessing bay 816a. The medical device is preferably suspended above the washing, rinsing or sterilizing fluid. The cassette 880 can be equipped with a plurality of clamping members 882 for holding the medical device being sterilized in position in the reprocessing bay 816a. The cassette can be removably positioned in the reprocessing bay 816a in a suspended orientation to the upper cassette guide 878a. As best shown in Figures 12 and 15, the cassette is preferably removably positioned between the upper cassette guide 878a and the lower cassette guide 878b. As best shown in Fig. 15, the cassette 880 can be configured to have an upper rotational member 886 and a lower rotational member 888

which are independently able to freely rotate about an axle member 890a, 890b which is fixedly secured to the upper and lower portions of the cassette 880. The upper rotational member 886 and the lower rotational member 888 are each provided with a guiding groove 892, 894, respectively. The guiding grooves 892, 894 are sized and configured to
5 complement the size and shape of the upper cassette guide 878a and the lower cassette guide 878b, respectively, for purpose of facilitating ease of movement of the cassette into and out of the reprocessing bay 816a.

In addition, the guiding groove 894 is sized and configured to complement the door guide 882 size and shape so as to guide and facilitate movement of the lower rotational
10 member 888 across the inner surface of the reprocessing bay door 846 when the bay door 846 is in the open position.

Extending into the upper portion of the reprocessing bay 816a is a medical device connector 896 which is configured to provide a fluid tight fitting for a wide variety of medical devices, such as endoscopes. It is within the concept of the present invention to
15 provide connection adapters that will permit a fluid tight fitting during pressure sterilization of the lumen of a wide variety of medical devices. Washing, rinsing and sterilizing fluids are provided to the medical device connector through tubing conduits as shown in Fig. 16.

The floor member 854 of the reprocessing bay 816a is configured to serve as a reservoir 898 for collection of fluids which have been sprayed onto or through the medical device
20 being reprocessed and sterilized in the reprocessing system 810. The reservoir can be equipped with a filtration system 900 of at least two levels of filtration. A sump drain 902 for collection of fluids is provided in the lower portion of the reservoir 898. The size of the reservoir 898 and the vertical positioning of the reprocessing bays 816 allows the reprocessing system 810 to operate and recirculate about 2-5 liters of sterilant. The
25 reprocessing system 810 preferably operates with about 3 liters of sterilant.

In operation, the preferred embodiment of the present invention provides for asynchronous reprocessing of two endoscopes with overlapping cycle time periods. Chemical components for the sterilant are heated and measured as they are moved to and mixed in the reaction chamber 836. The sterilant temperature is monitored and controlled and the reaction
30 of the chemical components in the reaction chamber 836 is timed under the control of a central processor 912. The sterilant's refractive index is measured to ensure the chemical reaction is complete and to verify the presence of the sterilant. Water is added to dilute the sterilant to the use-dilution concentration. Two endoscopes can be reprocessed and sterilized independently and asynchronously using reprocessing bays 816a, 816b. The endoscopes are

mounted on the cassettes 880 and connected to the medical device connector 896 through which the lumen of the endoscope will be pressure washed and sterilized. The reprocessing bay doors 846 are secured and the endoscopes are internally and externally washed with soap and water and rinsed. Just prior to the sterilization cycle, the endoscopes are rinsed with hot
5 water to ensure the sterilant will not be cooled upon contact with the endoscopes. The endoscopes are then sterilized internally and externally with sterilant prepared in the reaction chamber 836 just prior to use. The cleaning and sterilization of the endoscope lumen through the medical device connector 896 is assisted by a flow of liquid (soap and water, rinse water, and sterilant in turn) which receives a superimposed pulsating flow of air. This pulsating
10 flow of air causes the liquid flow to become severely unsteady resulting in a scrubbing action on the lumen wall of the endoscope.

Operation of the reprocessing system 810 is monitored by sensors, including those described above, which provide information to the central processor 912. The central processor 912 receives cycle program instructions from a user through the user interface 952.
15 The user interface can be equipped with any form of command signal keys or buttons as is well known in the art. Visual displays of user commands which are entered as well as central processor 912 responses, error messages, status notifications and the like can be presented for the user at the user interface 952. A printer capability can be included to permit the central processor 912 to provide written records of any aspect of reprocessing system operation to
20 the user. Printed records of specific endoscope sterilization can also be printed at the completion of a reprocessing and sterilization cycle. All aspects of the operation of the reprocessing system 810 can be controlled by the central processor 912, to include measuring and mixing of chemical components for the sterilant, metering of water to the reaction chamber 836 for sterilant dilution purposes, washing, rinsing and sterilizing cycles, self-
25 sterilizing, blockage detection and user notification, door ajar sensing and responsive operation termination, and other similar system monitoring and operational controls.

IN OPERATION

In operation, the valves 80, 82 alternate between a first position and a second position as
30 described above causing a first fluid flow path 110 and a second fluid flow path 112. In describing the fluid flow paths 110, 112, downstream is in the flow direction away from the distal end 52 of the umbilical section 28 and towards the distal end 54 of the insertion section 24.

Referring to Figures 3, 4, 7, and 8, in the preferred connection to an endoscope, when the device 10 is in the first position 106 causing a first fluid flow path 110, the first valve 80 is open to the fluid supply 84 allowing fluid to flow downstream through the CO₂ supply port 40, downstream through the umbilical CO₂ channel 22a, downstream through the CO₂ cylinder 36, downstream through the control CO₂ channel 22b, into the air channel 20, splitting into two flows, the first flow is upstream (first upstream flow) into the control air channel 20b, and the second flow is downstream into the insertion air channel 20c, downstream into the air/water channel 56, through the air/water nozzle 46 and exits the endoscope 12 to a drain 114 at about atmospheric pressure. The first upstream flow continues into the control air channel 20b and flows upstream into the air/water cylinder 32. From the air/water cylinder 32, the fluid splits and flows three ways; a) upstream through the umbilical water channel 16a and out the air/water supply port 42 through the second valve 82 to the drain line 88, b) upstream through the umbilical air channel 20a and out the air/water supply port 42 and air supply port 44 through the second valve 82 and to the drain line 88, and c) downstream through the insertion water channel 16c, downstream through the air/water channel 56, through the air/water nozzle 46 and exits the endoscope 12 to a drain 114 at about atmospheric pressure. The downstream flow through the insertion water channel 16c may flow upstream depending on the relative pressure loss between the various channels.

In a preferred connection to an endoscope, when the device is in the second position 108 causing a second fluid flow path 112, the second valve 82 is open to the fluid supply 84 allowing fluid to flow downstream through the air/water supply port 42 and air supply port 44 and downstream into both the umbilical water channel 16a and the umbilical air channel 20a meeting at the air/water cylinder 32. The fluid splits and flows downstream through control air channel 20b and downstream through the insertion water channel 16c, the flow continues through the insertion water channel 16c and downstream through the air/water channel 56 and through the air/water nozzle 46 and exits the endoscope 12 to a drain 114. The flow continues downstream through the control air channel 20b and splits and flows upstream into the CO₂ control channel 22b and downstream through the insertion air channel 20c. The flow continues downstream through the insertion air channel 20c through the air/water channel 56 and exits the endoscope 12 to a drain 114 at about atmospheric pressure. The flow continues upstream through the control CO₂ channel 22b, upstream through the CO₂ cylinder 36, upstream through the umbilical CO₂ channel 22a, upstream through the CO₂ supply port 40, and through the first valve 80. The fluid flows through the first valve 80 and to the drain line 88.

The second valve 82 may also remain completely closed when the first valve 80 is open to the fluid supply 84. If the second valve 82 remains closed, fluid will not flow as easily or at all from the air/water cylinder 32 through umbilical air channel 20a and umbilical water channel 16a.

5 In an alternative connection to an endoscope, as shown in Fig. 7, when the device is in the first position 206 causing a first fluid flow path 210, the first valve 80 is open to the fluid supply 84 allowing fluid to flow downstream through the air/water supply port 42 and air supply port 44 and downstream into both the umbilical water channel 16a and the umbilical air channel 20a meeting at the air/water cylinder 32. In this description of the flow, flow
10 through the CO₂ channel 22 is not included because the CO₂ valve 36 may be closed or there may not be a CO₂ channel. The fluid splits and flows three ways; a) downstream through control air channel 20b, b) downstream through the insertion water channel 16c, and c) through the air/water cylinder 32 to the second valve 82. The flow through the control air channel 20b flows downstream through the insertion air channel 20c, through the air/water
15 channel 56 and exits the endoscope 12 to a drain 114 at about atmospheric pressure. The flow through the insertion water channel 16c flows downstream through the air/water channel 56 and through the air/water nozzle 46 and exits the endoscope 12 to a drain 114 at about atmospheric pressure. The flow through the air/water cylinder 32 flows through the second valve 82 and to drain line 88.

20 In the alternative connection to an endoscope, as shown in Fig. 8, when the device is in the second position 208 causing a second fluid flow path 212, the second valve 82 is open to the fluid supply 84 allowing fluid to flow downstream through the air/water cylinder 32. In this description of the flow, flow through the CO₂ channel 22 is not included because the CO₂ valve 36 may be closed or there may not be a CO₂ channel. The fluid splits and flows four
25 ways; a) downstream through control air channel 20b, b) downstream through the insertion water channel 16c, and c) upstream into the umbilical water channel 16a, and d) upstream into the umbilical air channel 20a. The flow through the control air channel 20b flows downstream through the insertion air channel 20c, through the air/water channel 56 and exits the endoscope 12 to a drain 114 at about atmospheric pressure. The flow through the insertion
30 water channel 16c flows downstream through the air/water channel 56 and through the air/water nozzle 46 and exits the endoscope 12 to a drain 114 at about atmospheric pressure. The flow upstream into the umbilical water channel 16a flows out the air/water supply port 42 through the first valve 80 and to drain line 88. The flow upstream into the umbilical air

channel 20a flows out the air/water supply port 42 and the air supply port 44 through the first valve 80 and to drain line 88.

The suction channel 18 may also be cleaned or sterilized by using the above device 10. The suction channel 18 may be cleaned simultaneously by providing third and fourth valves 90,92 or separately by connecting to the first and second valves 80,82. The device 10 may have a third and a fourth position 140, 142, with the third and fourth position respectively the same as the first and second positions except that the third valve 90 replaces the first valve 80 and the fourth valve 92 replaces the second valve 82. The third valve 90 may be connected to the suction supply port 38 and the fourth valve 92 to the biopsy port 50 or alternatively to the suction control valve 34.

With the device in the third position 140 causing a third fluid flow path 136, fluid flows downstream through the suction supply port 38, downstream through the umbilical suction channel 18a, downstream through the suction cylinder 34, downstream through the control suction channel 18b, splitting into a upstream flow through the biopsy port 50 and through the fourth valve 92 to the drain line 88, and a downstream flow through the insertion suction channel 18c and exiting the suction opening 48 of the endoscope 12 to a drain 114 at about atmospheric pressure.

With the device in the fourth position 142 causing a fourth fluid flow path 138, fluid flows downstream through the biopsy port 50, splitting into a downstream flow through the insertion suction channel 18c and exiting through the suction opening 48, and splitting into an upstream flow through the control suction channel 18b, upstream through the suction cylinder 34, upstream through the umbilical suction channel 18a, upstream through the suction supply port 38 through the third valve 90 and to the drain line 88.

25

CLEANING AND STERILIZING METHODS

The apparatus and method in accordance with the present invention provides both a method of sterilization of tubular structures, in particular long, narrow, tubular structures, and a method of cleaning the lumens of a medical device.

30 The sterilization method broadly includes the sterilization of the interior of a tubular structure comprising: a) providing a tubular structure 94, 96, b) providing a sterilizing fluid 116 c) causing the sterilizing fluid 116 to flow at a positive pressure through the tubular structure 94, 96 in a first fluid flow path 110, and d) causing the sterilizing fluid 116 to reverse flow at a positive pressure through the tubular structure 94, 96 in a second fluid flow

path 112, so that at least part of the second fluid flow path 112 is opposite as the first fluid flow path 110.

The sterilization method may also include providing the sterilizing fluid 116 at a temperature preferably from about 20 degrees C to about 50 degrees C and most preferably about 40 degrees C to about 50 degrees C. The sterilizing fluid is preferably provided from about 1 minute to about 20 minutes and most preferably for about 10 minutes.

The sterilizing method may also provide that the sterilizing fluid 116 provided in the flow and reverse flow method of the present invention has a flow volume from preferably about 100 ml/min to about 1400 ml/min. The flow volume is preferably about 100 ml/min to about 250 ml/min for lumens with a diameter of about 1 mm to about 2 mm and about 600 ml/min to about 1400 ml/min for lumens with a diameter of about 3 mm to about 6 mm. The sterilizing fluid 116 provided in the flow and reverse flow method of the present invention has a flow velocity from preferably about 50 cm/sec to about 500 cm/sec and most preferably about 50 cm/sec to about 250 cm/sec. The sterilizing fluid 116 provided in the flow and reverse flow has a pressure preferably below about 20 psi and most preferably about 10 psi to about 20 psi.

The sterilization method may also include wherein the tubular structure 94, 96 has a diameter of less than about 6 mm.

The sterilization method may also include starting the first fluid flow path 110 and the second fluid flow path 112 in one end of a medical device.

The sterilization method may also include starting one fluid flow path 210, 212 in the control head or other central attachment point of a medical device.

The sterilization method may also include providing the device 10 of the present invention.

The sterilization method may also include controlling the flow and said reverse flow by a central processor.

The present invention also includes a method of cleaning a medical device with lumens 14. The cleaning method broadly includes a method of cleaning the lumens 14 of a medical device including a) providing a medical device with a first lumen 120 and a second lumen 122, each lumen 120, 122 having a proximal end 124, 128 and a distal end 126, 130 and the distal end 126, 130 of at least one of the lumens 120, 122 is open to a drain 114 at about atmospheric pressure; b) providing a cleaning fluid 86; c) causing the cleaning fluid 86 to flow through the lumens 120, 122 in a first fluid flow path 110 starting at the proximal end 124 of the first lumen 120; and d) causing the cleaning fluid 86 to reverse flow through the

lumens 120, 122 in a second fluid flow path 112 starting at the proximal end 128 of the second lumen 122, wherein at least part of the second fluid flow path 112 is opposite the first fluid flow path 110.

5 The cleaning method may also include providing a medical device with the proximal end 124, 128 of each lumen 120, 122 located in one end of the medical device.

The cleaning method may also include starting one fluid flow path 210, 212 in the control head or other central attachment point of a medical device.

The cleaning method may also include providing the device 10 of the present invention.

10 The cleaning method may also include draining the first fluid flow path 110 through the proximal end 128 of the second lumen 122 and draining the second fluid flow path 112 through the proximal end 124 of the first lumen 120.

The cleaning method may also provide that the cleaning fluid 86 provided in the flow and reverse flow has a flow volume from preferably about 100 ml/min to about 1400 ml/min. The flow volume is preferably about 100 ml/min to about 250 ml/min for lumens with a diameter of about 1 mm to about 2 mm and about 600 ml/min to about 1400 ml/min for lumens with a diameter of about 3 mm to about 6 mm. The cleaning fluid 86 provided in the flow and reverse flow has a flow velocity from preferably about 50 cm/sec to about 500 cm/sec and most preferably from about 50 cm/sec to about 250 cm/sec. The cleaning fluid 86 provided in the flowing and reverse flowing has a pressure preferably below about 20 psi and most preferably from about 10 psi to about 20 psi.

20 The cleaning method may also include providing the device 10 of the present invention.

The cleaning method may also provide controlling the flow and the reverse flow by a central processor.

25 The present device and method also improves sterilization of endoscopes. As shown in the following examples, complete sterilization of the lumens of endoscopes can be difficult, in particular, the CO₂ lumen of the endoscope. The CO₂ lumen typically has bends, connections, restrictions, and irregularities making it difficult to provide complete cleaning or sterilization of the CO₂ lumen.

30 The following tests show that the device and method of the present invention provides an unexpected improvement in the sterilization of the endoscope.

For the following experiments, the endoscope was coiled loosely and attached to a rack, which held it vertically. The control head was mounted so that the eyepiece was up and the control knobs were vertical. The suction, air/water, and CO₂ channels were inoculated with a total of 1-8 X 10⁶ bacterial endospores and dried for an hour. The endoscope was treated

with a performic acid based sterilant in a device that pumped sterilant through the channels and sprayed the exterior of the endoscope with sterilant. The endoscope was rinsed briefly and assayed for surviving organisms. If even one survivor was found, the endoscope was judged nonsterile. As shown in the table below, a large number of variables were tested in

5 our efforts to sterilize endoscopes consistently. The best results seemed to be obtained when the pressure (flow rate) in the lumens was increased to 20 psi, close to the maximum allowed. We noted that survivors were rarely found in the suction channel, the largest, least complex channel. Survivors were frequently found in the CO₂ channel, which has a small lumen and an intricate, constricted valve construction. Flowing sterilant in both directions

10 unexpectantly consistently eliminated all of the survivors in the endoscopes including in the CO₂ channel. As shown in the table, this procedure gave consistent sterilization even with a reduced pressure of 12 psi in the lumens.

TABLE I

5 Sterilizing endoscopes with performic acid based
sterilant, 10 minutes at 40 - 45°C

Connection point	Variable	Number scopes sterile/total tested
Control head	4 psi pressure in lumens	0/3
	10 psi pressure in lumens	1/2
	20 psi pressure in lumens	3/4
Light guide	4 psi pressure in lumens	0/3
	10 psi pressure in lumens	0/5
	20 psi pressure in lumens	5/8
Control head or light guide	Scope orientation -- lay flat	2/4
Control head	Scope orientation -- control knobs horizontal	0/2
	Scope orientation -- control head upside down	0/2
Light guide	Increase sterilant volume three-fold	1/3
	Prewarm scope to 45°C	1/2
Control head	Use restrictors to channel more flow to CO ₂ channel	2/7
Light guide	Connect to air/water only, flow to CO ₂ channel from control head	2/8
Control head or light guide	Interrupt sterilant flow with periodic air pulses	1/5
Light guide	Reverse flow in the CO ₂ channel	10/10

TABLE II

DETAILED DATA TABLE:

Improved Application of Liquids to Lumens by Reverse
5 Flow

Sterilization of endoscopes on an automatic endoscope reprocessor, 40 - 45°C, 15% performic acid based sterilant in RO water, 10-minute exposure.

Conn ^r	Chann press	Other	Number of survivors ^k							
			Suct ^a	CO ₂ ^b	ACI ^j	Ext	A/W port	CO ₂ valve	Suct Port	A/W port LG
CH		Connectors attached before inoculation, foamy, airpulse during sterilization (performic acid based sterilant without phosphoric)	0	0	0	0	0	0	0	0
			1	0	0	0	0	0	0	0
CH		Foamy, no airpulse	0	0	1	0	0	0	0	0
LG		Leaking plugs (modified ACI) at CH, foamy, performic acid based sterilant plus phosphoric acid	32	TNT C	TNTC	0	0	7	0	0
			2	66	8	0	0	0	0	0
			0	0	0	0	0	0	0	0
CH	10 psi	12 L sterilant, lay scopes flat	0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
CH	4 psi	Low foam by low pump speed (400 rpm)	0	0	1	0	0	0	0	0
			0	3	2	0	0	0	0	0
			0	2	0	0	0	0	0	0
LG	4 psi	Low foam	0	0	7	0	0	0	0	0
			0	1	0	0	0	0	0	0
			0	12	4	0	0	0	0	0

10

TABLE II Continued page 2 of 5

Conn ^r	Chann press	Other	Number of survivors ^r							
			Suct ^a	CO ₂ ^b	ACT ^j	Ext	A/W port	CO ₂ valve	Suct Port	A/W port LG
CH	10 psi	Standard position, raise channel pressure by restricting flow to spray arms (from this point forward)	0	0	0	0	0	0	0	0
			0	1	1	0	0	0	0	0
		Knobs up on control head	1	111		0	0	0	0	0
			0	1	0	0	0	0	0	0
		Upside down	0	38	17	0	0	0	0	0
			2	7	0	0	0	0	0	0
LG	10 psi		0	13	9	0	0	0	0	0
			0	2	0	0	0	0	0	0
LG	18 - 20 psi		0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	3	4	0	0	0	0	0
			0	1	0	0	0	0	0	0
			0	23	4	0	0	0	0	0
LG	18 - 20 psi	12 L sterilant	0	0	0	0	0	5	0	0
			0	0	0	0	0	0	0	ND
			1	0	0	0	0	0	0	0
LG	18 - 20	Dry at 45°C	2	TCT N	TN TC	0	0	0	0	0
			0	0	0	0	0	0	0	0
CH	18 - 20		0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	6	0	0	0	0	0
CH	18 - 20	Add restrictor to A/W connector on light guide end	0	2	17	0	0	0	0	0
			0	0	0	0	0	0	0	0

Table II Continued page 3 of 5

Conn ⁱ	Chann press	Other	Number of survivors ^k							
			Suct ^a	CO ₂ ^b	ACI ^j	Ext	A/W port	CO ₂ valve	Suct Port	A/W port LG
CH	18 - 20	As above. Sample A/W in both directions from control head, sample CO ₂ from control head to light guide as well as entire channel	0	P 24 ^g E 9	41 ^h	0	0	0	0	0
			0	P 6 E1 7	16 ⁱ	0	0	0	0	0
CH	18 - 20	Clamp on CO ₂ valve to hold it open, smaller restrictor on A/W connector on light guide end	0	2	6	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	1	0	0	0	0	0
LG	18 - 20	Connect suction & A/W only, tight restrictor on prong, standard inoculum	0	0	0	0	0	0	0	0
			0	1	0	0	0	0	0	0
LG		Connect suction, A/W, and CO ₂ , no restrictor, standard inoculum, run at 400 rpm as has been done above to reduce foam	0	2	2	0	0	0	0	0
			5	0	1	0	0	0	0	0
LG	9 - 10	Connect suction, A/W and CO ₂ , no restrictor, standard inoculum, run at 800 rpm, foamy	0	0	1	0	0	0	0	0
			0	1	0	0	0	0	0	0
			0	0	4	0	0	0	0	0

Table II Continued page 4 of 5

Conn ^f	Chann press	Other	Number of survivors ^k							
			Suct ^a	CO ₂ ^b	ACI ^j	Ext	A/W port	CO ₂ valve	Suct Port	A/W port LG
LG	9 - 10	As above except try to inoculate distal end only of air/water/CO ₂ channel (~0.3 ml inoculum rather than 5)	0	0	0	0	0	0	0	0
			0	2	2	0	0	0	0	0
LG	9 - 10	As above except lay scopes as flat as possible in rear of bay	0	1	0 A/W =3 ^j	0	0	0	0	0
			0	5	6 A/W =2	0	0	0	0	0
LG	13 - 14	Connect suction, A/W and air prong, standard inoculum, 800 rpm	0	0	0	0	0	0	0	0
			0	0	0	Mo ld	0	0	0	0
			0	17	33 A/W =4	0	0	0	0	0
			0	2	2	0	0	0	0	0
	10 - 12	Connect suction, A/W, restrictor on prong. Inoculate exterior- back of knob, insertion tube, control head	0	0	0	0	0	0	0	0
			0	28	14 A/W =1	0	0	0	0	0
	11 - 12	Purge with air for 5 sec in every minute of exposure, connect as above	0	6	1 A/W = 1	0	0	0	0	0
			0	4	1	0	0	0	0	0

Table II Continued page 5 of 5

Conn ^a	Chann press	Other	Number of survivors ^k							
			Suct ^a	CO ₂ ^b	ACI ^c	Ext	A/W port	CO ₂ valve	Suct Port	A/W port LG
	12 - 13	Purge with air for 15 sec every other minute of exposure (total of 4 times), connect as above	0	1	3	0	0	0	0	0
	10 - 13	Alternate direction of flow in CO ₂ channel every minute of exposure,	0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
			0	0	0	0	0	0	0	0
		No preheat, otherwise as above.	0	0	0	0	0	0	0	0

^aSuction channel flushed and brushed first

^b CO₂ channel flushed with syringe then all channels flushed with all-channel irrigator for ACI count

5 ^cThe tubing connection to the air/water and CO₂ channels was disconnected when the scope was partially removed from the chamber. It is possible that it came loose during the cycle.

^dThe exposure cycle was stopped for about 1 minute. The light guide end fell off the rack and pulled a tubing connection loose.

10 ^eFilters clogged during survivor recovery from neutralizer, most probably due to agar present in the neutralizer from previous use of bottle

^fLG = light guide, CH = control head

^gp = control head to light guide, E = entire length of channel

^hA/W only -- proximal (CH to LG) = 0, distal end (CH to nozzle) = 3

15 ⁱA/W proximal = 0, distal end = 0

^jAfter (and including) 46th test sampled the air and water channels from the light guide end to distal tip. This was done after the gas channel sampling but before the ACI. Results are reported only if there were survivors.

20 ^kIf the number of survivors is >0, the test failed.

Although the description of the preferred embodiment has been presented, it is contemplated that various changes, including those mentioned above, could be made without deviating from the spirit of the present invention. It is therefore desired that the present embodiment be considered in all respects as illustrative, not restrictive, and that reference be
5 made to the appended claims rather than to the foregoing description to indicate the scope of the invention.

CLAIMS

I claim:

1. A device for sterilizing or cleaning tubular structures comprising:

- a) a first valve and a second valve;
- 5 b) said first and second valves in fluid communication with a fluid supply maintained at a positive pressure;
- c) said first valve in fluid communication with a first tubular structure, the first tubular structure having a proximal end and a distal end, said first valve in fluid communication with the proximal end;
- 10 d) said second valve in fluid communication with a second tubular structure, the second tubular structure having a proximal end and a distal end, said second valve in fluid communication with the proximal end;
- e) the first tubular structure in fluid communication with the second tubular structure;
- 15 f) said first and second valves selectively switchable between a first position and a second position,
- g) said first position causing a first fluid flow path and said second position causing a second fluid flow path, wherein at least a part of said second fluid flow path is opposite said first fluid flow path;
- 20 h) wherein in said first position said first valve is open to the fluid supply and said second valve is closed to the fluid supply, and
- i) wherein in said second position said second valve is open to the fluid supply and said first valve is closed to the fluid supply.

25 2. The device of claim 1 wherein the distal end of at least one of the tubular structures is open to a drain at about atmospheric pressure.

3. The device of claim 1 wherein at least one of said valves is open to a drain line when said valve is closed to the fluid supply.

30

4. The device of claim 3 wherein in said first position said second valve is open to the drain line and in said second position said first valve is open to the drain line.

5. The device of claim 1 wherein the fluid supply is below about 20 psi.

6. The device of claim 5 wherein the fluid supply has a flow from about 50 cm/sec to about 500 cm/sec for about 1 minute to about 20 minutes.
7. The device of claim 1 wherein the fluid supply has a flow from about 100 ml/min to about 1400 ml/min and below about 20 psi.
8. The device of claim 1 wherein the tubular structures are lumens in a medical device.
9. The device of claim 8 wherein one of said fluid flow paths starts in a control head of the medical device.
10. The device of claim 8 wherein one of the tubular structures is a CO₂ lumen of an endoscope.
11. The device of claim 8 wherein the proximal end of the first tubular structure and the proximal end of the second tubular structure are located in one end of the medical device.
12. The device of claim 11 wherein said first fluid flow path is downstream except for upstream through a control air channel, upstream through an air/water cylinder, upstream through an umbilical air channel, upstream through an air/water supply port, upstream through said second valve, and upstream through an umbilical water channel; and said second fluid flow path is downstream except for upstream through a control CO₂ channel, upstream through a CO₂ cylinder, upstream through an umbilical CO₂ channel, upstream through a CO₂ supply port, and upstream through said first valve.
13. The device of claim 1 further comprising a third and a fourth valve, a third and a fourth tubular structure, and a third and a fourth position.
14. An automatic reprocessing device comprising the device of claim 1 wherein positioning of said valves is controlled by a central processor.
15. The device of claim 1 wherein the tubular structure is long and narrow.

16. The device of claim 1 wherein the tubular structure has a length and a diameter, the length from about 200 to about 8000 times the diameter.

17. The device of claim 1 wherein the fluid supply is a liquid.

5

18. A method of sterilizing a tubular structure comprising:

- a) providing a tubular structure;
- b) providing a sterilizing fluid;
- c) causing said sterilizing fluid to flow at a positive pressure through said tubular structure in a first fluid flow path; and
- d) causing said sterilizing fluid to reverse flow at a positive pressure through said tubular structure in a second fluid flow path, wherein at least part of said second fluid flow path is opposite said first fluid flow path.

10

15 19. The method of claim 18 wherein said sterilizing fluid is below about 50 degrees C and said sterilizing fluid is provided from about 1 minute to about 20 minutes.

20 20. The method of claim 18 wherein said tubular structure has a diameter of less than about 6 mm and wherein said flow and said reverse flow are from about 50 cm/second to about 500 cm/second and below about 20 psi.

21. The method of claim 18 wherein said flow and said reverse flow are from about 100 ml/min to about 1400 ml/min and below about 20 psi.

25 22. The method of claim 18 wherein said tubular structure is a lumen of a medical device.

23. The method of claim 22 wherein one of said fluid flow paths starts in a control head of said medical device.

30 24. The method of claim 22 wherein said first fluid flow path and said second fluid flow path start in one end of said medical device.

25. The method of claim 24 wherein said first fluid flow path is downstream except for upstream through a control air channel, upstream through an air/water cylinder, upstream

through an umbilical air channel, upstream through an air/water supply port, upstream through said second valve, and upstream through an umbilical water channel; and said second fluid flow path is downstream except for upstream through a control CO₂ channel, upstream through a CO₂ cylinder, upstream through an umbilical CO₂ channel, upstream through a CO₂ supply port, and upstream through said first valve.

26. The method of claim 18 further comprising providing the device of claim 1.

27. The method of claim 18 wherein said flow and said reverse flow are controlled by a central processor.

28. The method of claim 18 wherein said tubular structure is long and narrow.

29. The method of claim 18 wherein said tubular structure has a length and a diameter, said length from about 200 to about 8000 times said diameter.

30. The method of claim 18 wherein said sterilizing fluid is a liquid.

31. A method of cleaning the lumens of a medical device comprising:

- a) providing a medical device with a first lumen and a second lumen, said first and second lumens each having a proximal end and a distal end, and said distal end of at least one of said lumens open to a drain at about atmospheric pressure;
- b) providing a cleaning fluid;
- c) causing said cleaning fluid to flow at a positive pressure through said first and second lumens in a first fluid flow path, said first fluid flow path starting at said proximal end of said first lumen; and
- d) causing said cleaning fluid to reverse flow at a positive pressure through said first and second lumens in a second fluid flow path, said second fluid flow path starting at said proximal end of said second lumen, wherein at least part of said second fluid flow path is opposite said first fluid flow path.

32. The method of claim 31 wherein said proximal end of said first lumen and said proximal end of said second lumen are located in one end of said medical device.

33. The method of claim 31 wherein one of said fluid flow paths starts in a control head of said medical device.
- 5 34. The method of claim 31 wherein said first fluid flow path drains through said proximal end of said second lumen and said second fluid flow path drains through said proximal end of said first lumen.
- 10 35. The method of claim 31 wherein said flowing and said reverse flowing are from about 100 ml/min to about 1400 ml/min and below about 20 psi.
36. The method of claim 31 wherein said flowing and said reverse flowing are from about 50 cm/sec to about 500 cm/sec.
- 15 37. The method of claim 31 wherein said first fluid flow path is downstream except for upstream through a control air channel, upstream through an air/water cylinder, upstream through a umbilical air channel, upstream through an air/water supply port, upstream through said second valve, and upstream through a umbilical water channel; and said second fluid flow path is downstream except for upstream through a control CO₂ channel, 20 upstream through a CO₂ cylinder, upstream through a umbilical CO₂ channel, upstream through a CO₂ supply port, and upstream through said first valve.
38. The method of claim 31 further comprising providing the device of claim 1.
- 25 39. The method of claim 31 wherein said flowing and said reverse flowing are controlled by a central processor.
40. The method of claim 31 wherein said tubular structure is long and narrow.
- 30 41. The method of claim 31 wherein said tubular structure has a length and a diameter, said length from about 200 to about 8000 times said diameter.
42. The method of claim 31 wherein said cleaning fluid is a liquid.





1/36
Fig. 1*Fig. 2*

Fig. 3





4/36





Fig. 5**Fig. 6**

Fig. 7





7/36


Fig. 9

FIG. 9A	FIG. 9B	FIG. 9C	FIG. 9D
FIG. 9E	FIG. 9F	FIG. 9G	FIG. 9H

Fig. 10

FIG. 10A	FIG. 10B	FIG. 10C	FIG. 10D
FIG. 10E	FIG. 10F	FIG. 10G	FIG. 10H

8/36

Fig. 9A

SUBSTITUTE SHEET (RULE 26)

9/36


Fig. 9B

Fig. 9C





Fig. 9D

SUBSTITUTE SHEET (RULE 26)

12/36


Fig. 9E


Fig. 9F


Fig. 9G


Fig. 9H


Fig. 10A


Fig. 10B

Fig. 10C





Fig. 10D


Fig.10E

Fig.10F







Fig.10G

Fig.10H


24/36

Fig. 11




25/36

Fig. 12



26/36

Fig. 13



27/36

Fig. 15






Fig. 14




28/36

Fig.16

FIG.16A	FIG.16B	FIG.16C	FIG.16D
FIG.16E	FIG.16F	FIG.16G	FIG.16H


Fig. 16A

SUBSTITUTE SHEET (RULE 26)


Fig. 16B

31/36

Fig. 16C




SUBSTITUTE SHEET (RULE 26)


32/36
Fig. 16D


SUBSTITUTE SHEET (RULE 26)


33/36
Fig. 16E



34/36
Fig.16F



35/36
Fig.16G

36/36
Fig.16H

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/22532

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :B08B 3/00

US CL :134/169C

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 134/169C, 166C, 168C, 103.1, 171; 422/292, 300

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NONEElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)
NONE

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4,064,886 A (HECKELE) 27 DECEMBER 1977.	1-42
A	US 4,109,703 A (BABISH ET AL.) 29 AUGUST 1978.	1-42
A	US 4,161,979 A (STEARNS) 24 JULY 1979.	1-42
A	US 4,111,715 A (SPRENGLING ET AL.) 05 SEPTEMBER 1978.	1-42
A	US 4,299,244 A (HIRAI) 10 NOVEMBER 1981.	1-42
A	US 4,537,209 A (SASA) 27 AUGUST 1985.	1-42
X	US 4,667,691 A (SASA) 26 MAY 1987, see cols. 1-10.	18-30
A	US 4,763,678 A (OTT) 16 AUGUST 1988.	1-42

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search
18 DECEMBER 1999Date of mailing of the international search report
10 FEB 2000Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

FRANKIE L. STINSON

Telephone No. (703) 308-0661

DEBORAH THOMAS
PARALEGAL SPECIAL

INTERNATIONAL SEARCH REPORT**International application No.**
PCT/US99/22532**C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5,107,875 A (SUNDHOLM) 28 APRIL 1992.	1-42
A	US 5,551,462 A (BIERMAIER) 03 SEPTEMBER 1996	1-42
A	US 5,795,403 A (BIERMAIER) 18 AUGUST 1998.	1-42